

# PhD Course on Vehicle Dynamics Control. Yaw Damping via Front and Rear Steering

Paolo Falcone

Department of Signals and Systems,  
Chalmers University of Technology,  
Göteborg, Sweden  
`falcone@chalmers.se`

July 8, 2013

**CHALMERS**

# Lecture content

- ➊ Motivation
- ➋ Steering dynamics
- ➌ Decoupling of lateral and yaw dynamics
- ➍ Rear steering for yaw damping
- ➎ Extension of the decoupling to arbitrary mass distribution

**Note:** The following notes have been extracted from

- “Robust yaw damping of cars with front and rear wheel steering”, J. Ackermann, W. Sienel. *IEEE Transactions on Control Systems Technology*, vol. 1, no. 1, March 1993

# Lecture content

## ● Motivation

# Motivation


- Rear steering available. How to use it?



# Motivation

- Rear steering available. How to use it?

In



chose the velocity dependent pre-filter as

$$F_r(s, v) = K(v) \frac{1 + T_D(v)s}{1 + T_1(v)s},$$

where  $K < 0$  at low speed for better maneuverability in, e.g., parking. At high speed  $K > 0$ .

# Motivation

- ➊ Rear steering available. How to use it?
- ➋ Decoupling the driver's task of controlling the vehicle position w.r.t. a desired path from the yaw response

# Motivation


- ➊ Rear steering available. How to use it?
- ➋ Decoupling the driver's task of controlling the vehicle position w.r.t. a desired path from the yaw response

## Advantages

- ➊ The driver has to focus on the lateral motion only. Disturbances on the yaw dynamics are rejected by the rear-steering.
- ➋ The yaw damping can be varied without affecting the lateral vehicle behavior

# Motivation


- 1 Rear steering available. How to use it?
- 2 Decoupling the driver's task of controlling the vehicle position w.r.t. a desired path from the yaw response






# Motivation

- 1 Rear steering available. How to use it?
- 2 Decoupling the driver's task of controlling the vehicle position w.r.t. a desired path from the yaw response



# Motivation

- 1 Rear steering available. How to use it?
- 2 Decoupling the driver's task of controlling the vehicle position w.r.t. a desired path from the yaw response



- 3 Simple control design highlighting the properties of the yaw and lateral response to the front and rear steering

# Lecture content

- 1 Motivation
- 2 Steering dynamics

# Steering dynamics


## Assumption

The vehicle mass is distributed into two masses concentrated at the front and the rear axle.

# Steering dynamics

## Assumption


The vehicle mass is distributed into two masses concentrated at the front and the rear axle.



# Steering dynamics

## Assumption


The vehicle mass is distributed into two masses concentrated at the front and the rear axle.




In this case the inertia  $J$  and the mass  $m$  are related by

$$J = m l_r l_f$$

# Steering dynamics



# Steering dynamics




The linearized steering dynamics are given by

$$\begin{bmatrix} \dot{\beta} \\ \dot{r} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} \beta \\ r \end{bmatrix} + \begin{bmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{bmatrix} \begin{bmatrix} \delta_f \\ \delta_r \end{bmatrix},$$



# Steering dynamics



The linearized steering dynamics are given by

$$\begin{bmatrix} \dot{\beta} \\ \dot{r} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} \beta \\ r \end{bmatrix} + \begin{bmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{bmatrix} \begin{bmatrix} \delta_f \\ \delta_r \end{bmatrix},$$

where

$$\begin{aligned} a_{11} &= -(c_r + c_f)/mv, & a_{12} &= -1 + (c_r l_r - c_f l_f)/mv^2, \\ a_{21} &= (c_r l_r - c_f l_f)/m l_r l_f, & a_{22} &= -(c_r l_r^2 + c_f l_f^2)/m v l_r l_f, \\ b_{11} &= c_f/mv, & b_{12} &= c_r/mv, \\ b_{21} &= c_f/m l_r, & b_{22} &= -c_r/m l_f. \end{aligned}$$

# Steering dynamics

The characteristic polynomial of

$$\begin{bmatrix} \dot{\beta} \\ \dot{r} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} \beta \\ r \end{bmatrix} + \begin{bmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{bmatrix} \begin{bmatrix} \delta_f \\ \delta_r \end{bmatrix},$$

is given by

$$p(s) = \omega_0^2 + 2D_0\omega_0s + s^2$$

# Steering dynamics

The characteristic polynomial of

$$\begin{bmatrix} \dot{\beta} \\ \dot{r} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} \beta \\ r \end{bmatrix} + \begin{bmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{bmatrix} \begin{bmatrix} \delta_f \\ \delta_r \end{bmatrix},$$

is given by

$$p(s) = \omega_0^2 + 2D_0\omega_0 s + s^2$$

where

$$\omega_0^2 = \frac{c_r c_f \ell^2 + m v^2 (c_r \ell_r - c_f \ell_f)}{m^2 v^2 \ell_r \ell_f},$$

$$D_0 = \frac{\ell (c_r \ell_r + c_f \ell_f)}{2 \sqrt{\ell_r \ell_f} [c_r c_f \ell^2 + m v^2 (c_r \ell_r + c_f \ell_f)]}$$

# Lecture content

- 1 Motivation
- 2 Steering dynamics
- 3 Decoupling of lateral and yaw dynamics

# Decoupling of lateral and yaw dynamics

## Theorem

The steering control law given by  $H_f(s) = \frac{1}{s}$  is decoupling. I.e.,

- 1  $r$  and  $\delta_f$  are unobservable from  $a_f$ ,
- 2  $a_f$  is not controllable from  $\delta_r$ .

# Decoupling of lateral and yaw dynamics

## Theorem

The steering control law given by  $H_f(s) = \frac{1}{s}$  is decoupling. I.e.,

- 1  $r$  and  $\delta_f$  are unobservable from  $a_f$ ,
- 2  $a_f$  is not controllable from  $\delta_r$ .

## Proof

- 1 Augment the state-space model by adding  $\dot{\delta}_f = e_f$ .

# Decoupling of lateral and yaw dynamics

## Theorem

The steering control law given by  $H_f(s) = \frac{1}{s}$  is decoupling. I.e.,

- ❶  $r$  and  $\delta_f$  are unobservable from  $a_f$ ,
- ❷  $a_f$  is not controllable from  $\delta_r$ .

## Proof

- ❶ Augment the state-space model by adding  $\dot{\delta}_f = e_f$ .
- ❷ Transform the state-space model to the new state vector  $[a_f \ r \ \delta_f]$ , where

$$\begin{aligned} a_f &= v(r + \dot{\beta}) + \ell_f \dot{r} \\ &= v(r + a_{11}\beta + a_{12}r + b_{11}\delta_f + b_{12}\delta_r) \\ &\quad + \ell_f(a_{21}\beta + a_{22}r + b_{21}\delta_f) + b_{22}\delta_r \\ &= d_0(-\beta - \ell_f r/v + \delta_f), \quad d_0 = \ell_c f / m \ell_r \end{aligned}$$

# Decoupling of lateral and yaw dynamics

## Proof (Cont.)

- ③ Close the feedback loop with

$$\dot{\delta}_f = w_f - r$$



# Decoupling of lateral and yaw dynamics

## Proof (Cont.)

- Close the feedback loop with

$$\dot{\delta}_f = w_f - r$$

The model resulting from steps 1) - 3) is

$$\begin{bmatrix} \dot{a}_f \\ \dot{r} \\ \dot{\delta}_f \end{bmatrix} = \begin{bmatrix} \frac{d_{11}}{\quad} & | & 0 & 0 \\ \frac{d_{21}}{\quad} & | & d_{22} & d_{23} \\ 0 & | & -1 & 0 \end{bmatrix} \begin{bmatrix} a_f \\ r \\ \delta_f \end{bmatrix} + \begin{bmatrix} \frac{d_0}{\quad} & 0 \\ 0 & d_{22} \\ 1 & 0 \end{bmatrix} \begin{bmatrix} w_f \\ \delta_r \end{bmatrix},$$

$$a_f = \begin{bmatrix} 1 & | & 0 & 0 \end{bmatrix} \begin{bmatrix} a_f \\ r \\ \delta_f \end{bmatrix},$$

# Decoupling of lateral and yaw dynamics

## Proof (Cont.)

where

$$d_{11} = -\ell c_f / m v \ell_r$$

$$d_{21} = -(c_r \ell_r - c_f \ell_f) / c_f \ell_f \ell$$

$$d_{22} = -c_r \ell / m v \ell_f$$

$$d_{23} = c_r / m \ell_f$$

In conclusion

- 1  $r$  and  $\delta_f$  can't be observed from  $a_f$ ,
- 2  $a_f$  is not controllable from  $\delta_r$ .



# Decoupling of lateral and yaw dynamics

In conclusion, the steering dynamics can be split into the following two subsystems

# Decoupling of lateral and yaw dynamics

In conclusion, the steering dynamics can be split into the following two subsystems

- 1 Lateral motion of the front axle

$$\dot{a}_f = d_{11}a_f + d_0w_f \Rightarrow a_f(s) = G_f(s)F_f(s)\delta_S(s)$$

# Decoupling of lateral and yaw dynamics

In conclusion, the steering dynamics can be split into the following two subsystems

- 1 Lateral motion of the front axle

$$\dot{a}_f = d_{11}a_f + d_0w_f \Rightarrow a_f(s) = G_f(s)F_f(s)\delta_S(s)$$

- 2 Yaw motion

$$\begin{aligned} \begin{bmatrix} \dot{r} \\ \dot{\delta}_f \end{bmatrix} &= \begin{bmatrix} d_{22} & d_{23} \\ -1 & 0 \end{bmatrix} \begin{bmatrix} r \\ \delta_f \end{bmatrix} + \begin{bmatrix} d_{21} \\ 0 \end{bmatrix} a_f \\ &+ \begin{bmatrix} 0 & b_{22} \\ 1 & 0 \end{bmatrix} \begin{bmatrix} w_f \\ \delta_r \end{bmatrix}, \end{aligned}$$

# Decoupling of lateral and yaw dynamics

In conclusion, the steering dynamics can be splint into the following two subsystems

- 1 Lateral motion of the front axle

$$\dot{a}_f = d_{11}a_f + d_0w_f \Rightarrow a_f(s) = G_f(s)F_f(s)\delta_S(s)$$

- 2 Yaw motion

$$\begin{bmatrix} \dot{r} \\ \dot{\delta}_f \end{bmatrix} = \begin{bmatrix} d_{22} & d_{23} \\ -1 & 0 \end{bmatrix} \begin{bmatrix} r \\ \delta_f \end{bmatrix} + \begin{bmatrix} d_{21} \\ 0 \end{bmatrix} a_f \\ + \begin{bmatrix} 0 & b_{22} \\ 1 & 0 \end{bmatrix} \begin{bmatrix} w_f \\ \delta_r \end{bmatrix},$$

with characteristic polynomial

$$p_I(s) = \omega_I^2 + 2D_I\omega_I s + s^2,$$

and

$$\omega_I^2 = \frac{c_r}{m\ell_f}, \quad D_I = \frac{\ell}{2v} \sqrt{\frac{c_r}{m\ell_f}}.$$

# Decoupling of lateral and yaw dynamics

Compare now the damping of the uncontrolled and the decoupled systems. I.e.,  $D_I$  vs.  $D_0$ .

# Decoupling of lateral and yaw dynamics

Compare now the damping of the uncontrolled and the decoupled systems. I.e.,  $D_I$  vs.  $D_0$ .

Set  $D_I = D_0$  and solve for  $v$

$$v_\ell^2 = \frac{c_r^2 \ell_r \ell^2}{m \ell_f (c_f \ell_f + 3 c_r \ell_r)}$$



# Decoupling of lateral and yaw dynamics

Compare now the damping of the uncontrolled and the decoupled systems. I.e.,  $D_I$  vs.  $D_0$ .

Set  $D_I = D_0$  and solve for  $v$

$$v_\ell^2 = \frac{c_r^2 \ell_r \ell^2}{m \ell_f (c_f \ell_f + 3 c_r \ell_r)}$$

For  $v < v_\ell$  the decoupled vehicle has higher (better) damping

# Decoupling of lateral and yaw dynamics

Compare now the damping of the uncontrolled and the decoupled systems. I.e.,  $D_I$  vs.  $D_0$ .

Set  $D_I = D_0$  and solve for  $v$

$$v_\ell^2 = \frac{c_r^2 \ell_r \ell^2}{m \ell_f (c_f \ell_f + 3 c_r \ell_r)}$$

For  $v < v_\ell$  the decoupled vehicle has higher (better) damping

A comparison of  $\omega_0$  and  $\omega_I$  provides the limit speed

$$v_\omega = \ell \sqrt{\frac{c_r}{m \ell_f}}.$$

# Decoupling of lateral and yaw dynamics

Compare now the damping of the uncontrolled and the decoupled systems. I.e.,  $D_I$  vs.  $D_0$ .

Set  $D_I = D_0$  and solve for  $v$

$$v_\ell^2 = \frac{c_r^2 \ell_r \ell^2}{m \ell_f (c_f \ell_f + 3 c_r \ell_r)}$$

For  $v < v_\ell$  the decoupled vehicle has higher (better) damping

A comparison of  $\omega_0$  and  $\omega_I$  provides the limit speed

$$v_\omega = \ell \sqrt{\frac{c_r}{m \ell_f}}.$$

For  $v < v_\omega$  the decoupled vehicle has lower natural frequency.

# Decoupling of lateral and yaw dynamics

Compare now the damping of the uncontrolled and the decoupled systems. I.e.,  $D_I$  vs.  $D_0$ .

Set  $D_I = D_0$  and solve for  $v$

$$v_\ell^2 = \frac{c_r^2 \ell_r \ell^2}{m \ell_f (c_f \ell_f + 3 c_r \ell_r)}$$

For  $v < v_\ell$  the decoupled vehicle has higher (better) damping

A comparison of  $\omega_0$  and  $\omega_I$  provides the limit speed

$$v_\omega = \ell \sqrt{\frac{c_r}{m \ell_f}}.$$

For  $v < v_\omega$  the decoupled vehicle has lower natural frequency. Note that  $v_\omega$  is independent of the speed.

# Lecture content

- ➊ Motivation
- ➋ Steering dynamics
- ➌ Decoupling of lateral and yaw dynamics
- ➍ Rear steering for yaw damping

# Decoupling of lateral and yaw dynamics

We found  $D_I < D_0$  at high speed. I.e., the decoupled vehicle has worse damping at high speed

# Decoupling of lateral and yaw dynamics

We found  $D_I < D_0$  at high speed. I.e., the decoupled vehicle has worse damping at high speed

We now design a rear steering controller

# Decoupling of lateral and yaw dynamics

We found  $D_I < D_0$  at high speed. I.e., the decoupled vehicle has worse damping at high speed

We now design a rear steering controller

- rendering  $D_I$  independent of the speed,



# Decoupling of lateral and yaw dynamics

We found  $D_I < D_0$  at high speed. I.e., the decoupled vehicle has worse damping at high speed

We now design a rear steering controller

- 1 rendering  $D_I$  independent of the speed,
- 2 recovering the damping of the uncontrolled vehicle at high speed

# Decoupling of lateral and yaw dynamics

We found  $D_I < D_0$  at high speed. I.e., the decoupled vehicle has worse damping at high speed

We now design a rear steering controller

- 1 rendering  $D_I$  independent of the speed,
- 2 recovering the damping of the uncontrolled vehicle at high speed

## Theorem

The rear steering control law

$$\delta_r = (\ell/v - k_D)(w_r - r),$$

yields to speed independent eigenvalues of the yaw dynamics.

# Decoupling of lateral and yaw dynamics

## Proof.

Plug  $\delta_r = (\ell/v - k_D)(w_r - r)$  into the decoupled yaw and controller dynamics

$$\begin{aligned} \begin{bmatrix} \dot{r} \\ \dot{\delta}_f \end{bmatrix} &= \begin{bmatrix} d_{22} - (\ell/v - k_D)b_{22} & d_{23} \\ -1 & 0 \end{bmatrix} \begin{bmatrix} r \\ \delta_f \end{bmatrix} + \begin{bmatrix} d_{21} \\ 0 \end{bmatrix} a_f \\ &+ \begin{bmatrix} 0 & b_{22}(\ell/v - k_D) \\ 1 & 0 \end{bmatrix} \begin{bmatrix} w_f \\ w_r \end{bmatrix} \end{aligned}$$



# Decoupling of lateral and yaw dynamics

## Proof.

Plug  $\delta_r = (\ell/v - k_D)(w_r - r)$  into the decoupled yaw and controller dynamics

$$\begin{bmatrix} \dot{r} \\ \dot{\delta}_f \end{bmatrix} = \begin{bmatrix} d_{22} - (\ell/v - k_D)b_{22} & d_{23} \\ -1 & 0 \end{bmatrix} \begin{bmatrix} r \\ \delta_f \end{bmatrix} + \begin{bmatrix} d_{21} \\ 0 \end{bmatrix} a_f \\ + \begin{bmatrix} 0 & b_{22}(\ell/v - k_D) \\ 1 & 0 \end{bmatrix} \begin{bmatrix} w_f \\ w_r \end{bmatrix}$$

The characteristic polynomial becomes

$$p_{II}(s) = \omega_{II}^2 + 2D_{II}\omega_{II}s + s^2,$$



# Decoupling of lateral and yaw dynamics

## Proof.

Plug  $\delta_r = (\ell/v - k_D)(w_r - r)$  into the decoupled yaw and controller dynamics

$$\begin{aligned} \begin{bmatrix} \dot{r} \\ \dot{\delta}_f \end{bmatrix} &= \begin{bmatrix} d_{22} - (\ell/v - k_D)b_{22} & d_{23} \\ -1 & 0 \end{bmatrix} \begin{bmatrix} r \\ \delta_f \end{bmatrix} + \begin{bmatrix} d_{21} \\ 0 \end{bmatrix} a_f \\ &+ \begin{bmatrix} 0 & b_{22}(\ell/v - k_D) \\ 1 & 0 \end{bmatrix} \begin{bmatrix} w_f \\ w_r \end{bmatrix} \end{aligned}$$

The characteristic polynomial becomes

$$p_{II}(s) = \omega_{II}^2 + 2D_{II}\omega_{II}s + s^2,$$

with

$$\omega_{II}^2 = \frac{c_r}{m\ell_f}, \quad D_{II} = \frac{k_D}{2} \sqrt{\frac{c_r}{m\ell_f}} = \frac{k_D\omega_{II}}{2}.$$



# Lecture content

- ➊ Motivation
- ➋ Steering dynamics
- ➌ Decoupling of lateral and yaw dynamics
- ➍ Rear steering for yaw damping
- ➎ Extension of the decoupling to arbitrary mass distribution

# Decoupling with arbitrary mass distribution

Recall that the decoupling front steering control law has been derived under the following

# Decoupling with arbitrary mass distribution

Recall that the decoupling front steering control law has been derived under the following

## Assumption

The vehicle mass is distributed into two masses concentrated at the front and the rear axle.



# Decoupling with arbitrary mass distribution

Recall that the decoupling front steering control law has been derived under the following

## Assumption

The vehicle mass is distributed into two masses concentrated at the front and the rear axle.

The above assumption is equivalent to  $J = m\ell_f\ell_r$

# Decoupling with arbitrary mass distribution


Recall that the decoupling front steering control law has been derived under the following

## Assumption

The vehicle mass is distributed into two masses concentrated at the front and the rear axle.

The above assumption is equivalent to  $J = m\ell_f\ell_r$

In case of arbitrary mass distribution



# Decoupling with arbitrary mass distribution

Recall that the decoupling front steering control law has been derived under the following


## Assumption

The vehicle mass is distributed into two masses concentrated at the front and the rear axle.

The above assumption is equivalent to  $J = m\ell_f\ell_r$

In case of arbitrary mass distribution

$$\begin{aligned}m &= m_1 + m_2, \quad J = m_1\ell_1^2 + m_2\ell_r^2 \\ m_1\ell_1 &= m_2\ell_r, \quad J = m_2\ell_1\ell_r + m_1\ell_1\ell_r \\ J &= m\ell_1\ell_r\end{aligned}$$



# Decoupling with arbitrary mass distribution

Recall that the decoupling front steering control law has been derived under the following

## Assumption


The vehicle mass is distributed into two masses concentrated at the front and the rear axle.

The above assumption is equivalent to  $J = m\ell_f\ell_r$

In case of arbitrary mass distribution

$$\begin{aligned}m &= m_1 + m_2, \quad J = m_1\ell_1^2 + m_2\ell_r^2 \\ m_1\ell_1 &= m_2\ell_r, \quad J = m_2\ell_1\ell_r + m_1\ell_1\ell_r \\ J &= m\ell_1\ell_r\end{aligned}$$

$$m_1 = \frac{m^2\ell_r^2}{J + m\ell_r^2}, \quad m_2 = \frac{mJ}{J + m\ell_r^2}$$



# Decoupling with arbitrary mass distribution

Assume  $\dot{v} = 0$  and small  $\delta_f$ . Write the lateral and yaw dynamics as

$$\begin{bmatrix} mv(\dot{\beta} + r) \\ J\dot{r} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \ell_f & -\ell_r \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix}.$$

# Decoupling with arbitrary mass distribution

Assume  $\dot{v} = 0$  and small  $\delta_f$ . Write the lateral and yaw dynamics as

$$\begin{bmatrix} mv(\dot{\beta} + r) \\ J\dot{r} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \ell_f & -\ell_r \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix}.$$

Recall that

$$f_f(0) = 0 \quad f_f(\alpha_f)/\alpha_f > 0 \quad \alpha_f = \delta_f - \beta_f$$

$$\alpha_r = -\beta_r \quad \alpha_r = \delta_r - \beta_r$$

# Decoupling with arbitrary mass distribution

Assume  $\dot{v} = 0$  and small  $\delta_f$ . Write the lateral and yaw dynamics as

$$\begin{bmatrix} mv(\dot{\beta} + r) \\ J\dot{r} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \ell_f & -\ell_r \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix}.$$

Recall that

$$f_f(0) = 0 \quad f_f(\alpha_f)/\alpha_f > 0 \quad \alpha_f = \delta_f - \beta_f$$

$$\alpha_r = -\beta_r \quad \alpha_r = \delta_r - \beta_r$$

Introduce now  $\beta_1 = \beta + \frac{\ell_1 r}{v}$  as state variable

$$\begin{bmatrix} mv(\dot{\beta}_1 + r - \frac{\ell_1 \dot{r}}{v}) \\ J\dot{r} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \ell_f & -\ell_r \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix},$$

# Decoupling with arbitrary mass distribution

Assume  $\dot{v} = 0$  and small  $\delta_f$ . Write the lateral and yaw dynamics as

$$\begin{bmatrix} mv(\dot{\beta} + r) \\ J\dot{r} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \ell_f & -\ell_r \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix}.$$

Recall that

$$f_f(0) = 0 \quad f_f(\alpha_f)/\alpha_f > 0 \quad \alpha_f = \delta_f - \beta_f$$

$$\alpha_r = -\beta_r \quad \alpha_r = \delta_r - \beta_r$$

Introduce now  $\beta_1 = \beta + \frac{\ell_1 r}{v}$  as state variable

$$\begin{bmatrix} mv(\dot{\beta}_1 + r - \frac{\ell_1 \dot{r}}{v}) \\ J\dot{r} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ \ell_f & -\ell_r \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix},$$

with

$$\alpha_f = \delta_f - \beta_1 - r \frac{\ell_f - \ell_1}{v}, \quad \alpha_r = -\beta_1 + r \frac{\ell_r + \ell_1}{v}$$



# Decoupling with arbitrary mass distribution

The dynamics of the yaw and the side slip of mass  $m_1$  can be rearranged as

$$\begin{bmatrix} \dot{\beta}_1 \\ \dot{r} \end{bmatrix} = \begin{bmatrix} \ell/mv\ell_r & 0 \\ \ell_f/J & -\ell_r/J \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix} - \begin{bmatrix} 1 \\ 0 \end{bmatrix} r$$

# Decoupling with arbitrary mass distribution

The dynamics of the yaw and the side slip of mass  $m_1$  can be rearranged as

$$\begin{bmatrix} \dot{\beta}_1 \\ \dot{r} \end{bmatrix} = \begin{bmatrix} \ell/mv\ell_r & 0 \\ \ell_f/J & -\ell_r/J \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix} - \begin{bmatrix} 1 \\ 0 \end{bmatrix} r$$

Observe that,

# Decoupling with arbitrary mass distribution

The dynamics of the yaw and the side slip of mass  $m_1$  can be rearranged as

$$\begin{bmatrix} \dot{\beta}_1 \\ \dot{r} \end{bmatrix} = \begin{bmatrix} \ell/mv\ell_r & 0 \\ \ell_f/J & -\ell_r/J \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix} - \begin{bmatrix} 1 \\ 0 \end{bmatrix} r$$

Observe that,

- the rear tire force  $f_r$  has no direct effect on  $\beta_1$

## Theorem

The front steering control law

$$\dot{\delta}_f = w_f - r + \dot{r} \frac{\ell_f - \ell_1}{v},$$

renders the yaw rate  $r$  unobservable from the front tire slip angle  $\alpha_f$ .

# Decoupling with arbitrary mass distribution

The dynamics of the yaw and the side slip of mass  $m_1$  can be rearranged as

$$\begin{bmatrix} \dot{\beta}_1 \\ \dot{r} \end{bmatrix} = \begin{bmatrix} \ell/mv\ell_r & 0 \\ \ell_f/J & -\ell_r/J \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix} - \begin{bmatrix} 1 \\ 0 \end{bmatrix} r$$

Observe that,

- 1 the rear tire force  $f_r$  has no direct effect on  $\beta_1$
- 2  $f_r$  has an indirect effect on  $\beta_1$  through  $r$

## Theorem

The front steering control law

$$\dot{\delta}_f = w_f - r + \dot{r} \frac{\ell_f - \ell_1}{v},$$

renders the yaw rate  $r$  unobservable from the front tire slip angle  $\alpha_f$ .

# Decoupling with arbitrary mass distribution

The dynamics of the yaw and the side slip of mass  $m_1$  can be rearranged as

$$\begin{bmatrix} \dot{\beta}_1 \\ \dot{r} \end{bmatrix} = \begin{bmatrix} \ell/mv\ell_r & 0 \\ \ell_f/J & -\ell_r/J \end{bmatrix} \begin{bmatrix} f_f(\alpha_f) \\ f_r(\alpha_r) \end{bmatrix} - \begin{bmatrix} 1 \\ 0 \end{bmatrix} r$$

Observe that,

- ❶ the rear tire force  $f_r$  has no direct effect on  $\beta_1$
- ❷  $f_r$  has an indirect effect on  $\beta_1$  through  $r$
- ❸  $r$  enters linearly in the  $\beta_1$  dynamics

## Theorem

The front steering control law

$$\dot{\delta}_f = w_f - r + \dot{r} \frac{\ell_f - \ell_1}{v},$$

renders the yaw rate  $r$  unobservable from the front tire slip angle  $\alpha_f$ .

# Decoupling with arbitrary mass distribution

Proof.

Recall that  $\alpha_f = \delta_f - \beta_1 - r \frac{\ell_f - \ell_1}{v}$ .



# Decoupling with arbitrary mass distribution

Proof.

Recall that  $\alpha_f = \delta_f - \beta_1 - r \frac{\ell_f - \ell_1}{v}$ . Differentiate  $\alpha_f$

$$\begin{aligned}\dot{\alpha}_f &= \dot{\delta}_f - \dot{\beta}_1 - \dot{r} \frac{\ell_f - \ell_1}{v} \\ &= \dot{\delta}_f - \frac{\ell}{mv\ell_r} f_f(\alpha_f) + r - \dot{r} \frac{\ell_f - \ell_1}{v}\end{aligned}$$



# Decoupling with arbitrary mass distribution

Proof.

Recall that  $\alpha_f = \delta_f - \beta_1 - r \frac{\ell_f - \ell_1}{v}$ . Differentiate  $\alpha_f$

$$\begin{aligned}\dot{\alpha}_f &= \dot{\delta}_f - \dot{\beta}_1 - \dot{r} \frac{\ell_f - \ell_1}{v} \\ &= \dot{\delta}_f - \frac{\ell}{mv\ell_r} f_f(\alpha_f) + r - \dot{r} \frac{\ell_f - \ell_1}{v}\end{aligned}$$

Plug  $\dot{\delta}_f = w_f - r + \dot{r} \frac{\ell_f - \ell_1}{v}$  in the expression of  $\dot{\alpha}_f$

$$\dot{\alpha}_f = w_f - \frac{\ell}{mv\ell_r} f_f(\alpha_f)$$





# Decoupling with arbitrary mass distribution

Observe that, under the

## Assumption

The vehicle mass is distributed into two masses concentrated at the front and the rear axle.

$\ell_1 = \ell_f$  and the front steering control law reduces to the previous.