



 POLITECNICO DI MILANO



XVII Scuola Nazionale di Dottorato – Bertinoro, 8-13 luglio, 2013

Longitudinal dynamics: introduction and problem setting

Mara Tanelli
mara.tanelli@polimi.it
<http://move.dei.polimi.it/>



Main references:

TA Johansen, I. Petersen, Kalkkuhl J., J. Lüdemann (2003). "Gain-Scheduled Wheel Slip Control in Automotive Brake Systems." IEEE Transactions on Control Systems Technology, Vol 11, No. 6, pp.799-811.

Savaresi s.m., M. Tanelli, C. Cantoni (2007). Mixed slip-deceleration control in automotive braking systems. ASME Transactions: Journal of Dynamic Systems, Measurement and Control, Vol.129, No. 1, pp.20-31 [2008 ASME Dynamic Systems and Control Rudolf Kalman Best Paper Award][Patent]





References - Book

List of Abbreviations xvii

Part I Braking Control Systems Design: Introduction and Modelling

1	Introduction to Active Braking Control Systems	3
1.1	Introduction	3
1.2	ABS Systems: a Historical Perspective	4
1.3	The Actuators: Main Technologies and Functional Description	5
1.4	The X-by-wire Approach	10
1.5	State-of-the-art in Active Braking Control Design	12
1.6	Recent Evolutions: Brake-based Global Chassis Control	14
1.7	Summary	16

2	Control-oriented Models of Braking Dynamics	17
2.1	Introduction	17
2.2	Tyre-road Contact Forces	17
2.2.1	Friction Models	20
2.2.2	Relaxation Dynamics	24
2.3	The Single-corner Model	24
2.4	The Double-corner Model	27
2.5	Linearised Models and Dynamic Analysis	30
2.5.1	Single-corner Model Analysis	31
2.5.2	Double-corner Model Analysis	41
2.6	Summary	52

Part II Braking Control Systems Design: Basic Solutions

3	Braking Control Systems Design: Actuators with Continuous Dynamics	55
3.1	Introduction	55

3.2	Wheel Slip Control	55
3.3	Wheel Deceleration Control	58
3.4	Linear Wheel Slip Controller Design	60
3.5	Effects of Actuator Dynamics	64
3.6	Performance Analysis: a Numerical Example	66
3.7	Activation and Deactivation Logic	69
3.7.1	Activation Conditions	70
3.7.2	De-activation Conditions	71
3.8	Slip Controller Analysis Based on the Double-corner Model	74
3.8.1	Closed-loop Stability Analysis	74
3.8.2	Controlling the Rear Wheel: Slip <i>versus</i> Relative Slip Control	77
3.8.3	Wheel Slip Control on Curves	80
3.9	Summary	83

4	Braking Control Systems Design: Actuators with Discrete Dynamics	85
4.1	Introduction	85
4.2	Problem Setting	86
4.3	Existence and Stability of Limit Cycles	90
4.4	Limit Cycle Stability Analysis	99
4.5	Effects of the Actuator Rate-limit Variation	100
4.6	Summary of the Actuators' Performance	102
4.7	Summary	103

5	Longitudinal Wheel Slip Estimation	107
5.1	Introduction	107
5.2	Interaction Between Braking Control and Speed Estimation	108
5.3	A Solution for Vehicle Speed Estimation	112
5.4	Performance Evaluation of the Estimation Algorithm	116
5.5	Summary	119

Part III Braking Control Systems Design: Advanced Solutions

6	Mixed Slip and Deceleration Control	123
6.1	Introduction	123
6.2	Mixed Slip-deceleration Control	124
6.2.1	Analysis of the Open-loop Dynamics	126
6.2.2	Closed-loop Stability for MSD Control	127
6.3	Disturbance Analysis of Slip Control and MSD Control	130
6.4	Steady-state Slip Values in MSD Control	136
6.5	Numerical Analysis	138
6.6	Summary	141

7	Nonlinear Wheel Slip Control Design	143
7.1	Introduction	143
7.2	Assumptions	144
7.3	Lyapunov-based Slip Control	144
7.4	Numerical Analysis	154
7.5	Summary	156


8	Identification of Tyre-road Friction Conditions	159
8.1	Introduction	159
8.2	Detection of the Friction-curve Peak by Wheel-deceleration Measurements	160
8.2.1	Online Detection of the Friction Curve Slope Sign	161
8.2.2	ABS Supervisory Control Logic	163
8.2.3	Experimental Results	164
8.3	Real-time Identification of Tyre-road Friction Conditions	166
8.3.1	Identification Strategies	169
8.3.2	Numerical Analysis	171
8.3.3	Experimental Results	177
8.4	Direct Estimation of Contact Forces <i>via</i> In-tyre Sensors	182
8.4.1	Introduction	183
8.4.2	Experimental Set Up	184
8.4.3	Main Concept	186
8.4.4	Signal Processing	188
8.4.5	Experimental Results	195
8.5	Summary	198

A	Analysis and Synthesis Tools for Dynamical Systems	203
A.1	Introduction	203
A.2	Dynamical Systems Analysis	204
A.2.1	Stability of Equilibria: Lyapunov's Theory	207
A.2.2	A Special Case: Second-order Dynamical Systems	215
A.3	Nonlinear Design Tools	225
A.4	Summary	229

B	Signal Processing of Wheel Encoders	231
B.1	Introduction	231
B.2	Wheel Encoders' Signals	231
B.2.1	Velocity Estimation Algorithms	233
B.2.2	Wheel Radius Calibration	240
B.3	Analysis and Filtering of the Wheel Encoders' Signal	242
B.4	Summary	244

References 247

Index 255




The following slides are adapted from those used in the course
“Automazione nei mezzi di trasporto”

(M.Sc. course at the Politecnico di Milano, Prof. Sergio M. Savaresi)



6dof...



Braking&traction-control
= longitudinal (forward)
movement




Tire-road contact forces: introduction

Separable (along the road surface) into two orthogonal components: longitudinal (F_l or F_x) and lateral/side (F_s or F_y)

$$F_l(\lambda, \alpha, F_z, \gamma) \quad \mu_l := \frac{F_l}{F_z}$$
$$F_s(\lambda, \alpha, F_z, \gamma) \quad \mu_s := \frac{F_s}{F_z}$$

μ : friction coefficient



λ = longitudinal slip

α = Slip angle


γ = Camber angle

F_z = Vertical load



Road-tire contact forces: the definition of (longitudinal) slip

v : body speed
 r : rolling radius
 ω : angular wheel speed




$$\lambda = \frac{v - \omega r}{\max\{v, \omega r\}}$$

If brake:

$$\lambda := \frac{v - \omega r}{v}$$

If traction:

$$\lambda = \frac{-(v - \omega r)}{\omega r}$$



"SLIP" $\lambda = \frac{\text{Body speed} - \text{Wheel speed}}{\text{Body speed}}$




Linearity with respect to F_z - **REMARK**

Consider the simplified relationship ($\alpha=0$; $\gamma=0$)

$$F_x(F_z, \lambda)$$

Usually it is approximated by assuming a **LINEAR** relationship:

$$F_x = F_z \mu(\lambda)$$





Tire-road contact forces: dynamics



$F_l(\lambda, \alpha, F_z, \gamma)$
 $F_s(\lambda, \alpha, F_z, \gamma)$ are algebraic relations


The real behavior is dynamic, due to the transients in tire deformation.

Dynamics (simplified) model:

$$\left[\frac{\left(\frac{v_w}{s_{0l}} \right)}{s + \left(\frac{v_w}{s_{0l}} \right)} \right]$$


wheel speed

relaxation length (about 1/2 circumference)





Contact forces: longitudinal



Dry surface
Camber: null

if there is no slip the
longitudinal force is zero


force increases linearly
up to values of λ of about
0.1-0.15

beyond the maximum:
slope sign changes

Increasing side-slip
angle:
- Reduction of
longitudinal force
- The maximum point
moves forward




Experimental results





Contact forces: lateral



Dry surface
Camber: null

if there is no side-slip angle: lateral force is zero

Force increases with increasing side-slip angle


Force reaches its maximum at $\lambda = 0$

If wheels locked ($\lambda = 1$) lateral force vanishes (total loss of directionality)


Note: for fixed α , varying λ transfers force to/from longitudinal to/from lateral force



g-g plots




Senna, '87, Adelaide



Herbert, 93, Silverstone



Dependence of the contact forces from the road surface (longitudinal force)



Variation of the shape

Variation of the peak



Formulas for modeling tire-road contact forces


Year	Model Name	Model Properties	Features
	Piecewise Linear Model	Empirical	1. Cannot accurately fit curves 2. Easy to identify
1993	Burckhardt Model	Semi-Empirical	1. Can accurately fit curves 2. Has some revised formula
1994	Rill Model	Semi-Empirical	Easy to identify
1987	Magic Formula	Semi-Empirical	1. Can accurately fit curves 2. Has lost of revised formula 3. Can employ different factors
1977	Dahl Model	Analytical	1. Can describe Coulomb friction. 2. Can produces smooth transition around zero velocity
1991	Bliman-Sorine Model	Analytical	Can capture the Stribeck effect in addition to Dahl model
1995	LuGre Model	Analytical	Can combine pre-sliding & sliding in addition to Bliman-Sorine Model

Integrated longitudinal and lateral tire / road friction modeling and monitoring for vehicle motion control, Li Li, Fei-Yue Wang; Qunzhi Zhou, IEEE Transactions on Intelligent Transportation Systems, Volume 7, Issue 1, March 2006 Page (s): 1-19



Burckhardt formula for longitudinal force


$$\mu(\lambda; \theta_r) = \theta_{r1} (1 - \exp(-\lambda \theta_{r2})) - \lambda \theta_{r3}$$



	θ_{r1}	θ_{r2}	θ_{r3}
Asphalt, dry	28.01	23.99	00:52
Asphalt, wet	0.86	33.82	12:35
Cobblestones, dry	1:37	6:46	0.67
Snow	00:19	94.13	12:06



Problem of brake/traction control: summary





Straight brake / acceleration:
ideal λ is around the peak.

Three issues (ABS/TC motivations):

$\lambda=1$: loss of brake/traction (- 30%)



$\lambda=1$: NO lateral forces

After the peak ($\lambda > 0.15$): open-loop instability!





The problem of “TC”: why useful?




Un po' di slittamento non fa mal male

La definizione di slittamento è legata al fatto che la deformazione del pneumatico, necessaria a produrre l'aderenza a terra, tende a tradursi in una velocità periferica superiore a quella di effettivo avanzamento del veicolo. Solo se le due velocità coincidono, lo slittamento è pari a zero; all'estremo opposto, quando la ruota si muove a moto fermo lo slittamento è totale (100%). In uscita di curva (sopra), la situazione è intermedia.





The dilemma of the driver when cornering ...





ABS: History ...

One of the first patents "An Improved Safety Device for Preventing the Jamming of the Running Wheels of Automobiles When Braking ") was filed in Europe in 1932, while a similar result ('Apparatus for Preventing Wheel Sliding ') was obtained in the United States in 1936.

In the railway industry: first application around 1943

The aeronautical field: 1947, B-47 bombers to avoid an excessive increase in braking distance on icy surfaces and damage to the tires.

In 1968: airplanes 'Thunderbirds'.

Ford, Chrysler and Cadillac offered the ABS on a limited number of vehicles. Pneumatic Actuators: very slow and increased stopping distances.

Germany: a joint venture formed by Telefunken and Bendix tried to market a system called ABS Tekline. But the electronic design and manufacturing technologies were too young and unreliable.

1978: Bosch announces "Anti-Blockier System" (hence the acronym ABS).

In the same year, Mercedes Benz offered for the first time the ABS as an option for its high-end (S-class) cars.

Association of European Car Manufacturers (ACEA): equipment required for all new cars registered from 1 July 2004.


ABS will become mandatory for motorcycles in Europe since 2017.

1936	A Robert Bosch viene riconosciuto il brevetto numero 671925 per un dispositivo definito «anti incollaggio dei freni».
1965	Viene avviato lo sviluppo dell'impianto Abs regolato elettronicamente.
1978	Comincia la produzione per il montaggio sulla Mercedes «classe S» e successivamente sulla BMW «serie 7». È un optional molto costoso.
1986	Viene fornito il milionesimo impianto.
1987	Al dispositivo viene aggiunta la funzione Asr, ossia l'antipattinamento in accelerazione.
1991	La Bosch presenta l'«Abs/Asr 5», più leggero, compatto e meno costoso, quindi adatto anche alle vetture medie.
1995	Si raggiungono i 20 milioni d'impianti prodotti.
2003	La produzione Bosch tocca la soglia dei 100 milioni di pezzi.
LUGLIO 2004	Entro questa data tutte le auto nuove vendute in Europa dovranno avere di serie l'Abs, come deciso volontariamente dai Costruttori Acea.




Actuators (traditional layout)

HAB: Hydraulic Actuated Brakes (Increase, hold, decrease)





Actuation layout in brake-by-wire architectures


Traditional architecture



Pure brake-by-wire EM architecture



brake-by-wire hybrid architecture




The traditional hydraulic structure is preserved



Measurement problem: slip estimation


Control Problem: slip tracking

- with advanced BBW architecture
- with a traditional on-off-valve architecture



Problems:

- which is the best target slip?
- knowledge of friction conditions?



- 1) Simplified (control-oriented) model
- 2) Dynamic analysis
- 3) Controller design



"Single-corner" model

$$\begin{cases} J\dot{\omega} = rF_x - T_b \\ m\dot{v} = -F_x \end{cases}$$


$$F_x = F_z \mu(\lambda, \alpha; \theta_r)$$

$$\lambda = (v - \omega r) / v = 1 - r\omega / v$$

$$\begin{cases} J\dot{\omega} = rF_z \mu\left(\frac{v - \omega r}{v}\right) - T_b \\ m\dot{v} = -F_z \mu\left(\frac{v - \omega r}{v}\right) \end{cases}$$

- ω : angular speed of the wheel ([rad/s]; $\omega > 0$ is assumed);
- v : longitudinal speed of the vehicle body;
- T_b : braking torque (control/input variable);
- F_x : longitudinal road-tire contact force;
- F_z : vertical road-tire contact force;
- J, m and r are the momentum of inertia of the wheel, the quarter-car mass, and the wheel radius

(e.g. $J = 1 \text{ Kg m}^2$, $m = 225 \text{ Kg}$, $r = 0.28 \text{ m}$).



SISO system, 2nd order ($n=2$), non-linear, time-invariant